




KONICA MINOLTA



## **bizhub C652** FULL COLOR\_PRINTER\_COPIER\_SCANNER\_FAX\_

**THE BIZHUB THAT DOES COLOR FASTER AND BETTER.** With extraordinary performance and unique styling, the bizhub C652 is the color solution your workflow demands. You'll have spectacular color documents at 50 ppm output speed that never slows you down – plus cost-effective 65 ppm B&W printing for everyday document demands. You'll also have best-in-class technology, with the built-in Emperon® print system for full print/scan/copy functionality with native XPS and Windows Vista support. Faster scanning to multiple destinations helps you save, access and distribute information more easily. A large capacity cassette accommodates letter-size paper – and a new adjustable paper deck option handles sizes from 8-1/2" x 11" to 12" x 18". You'll also have all the options you need: 100-sheet stapling, hole-punching, booklet-making, high-speed fax and advanced Fiery® image control for intensive color graphics applications.



CONNECT \_ COMMUNICATE \_ CONTROL



- ▶ FAST WARM-UP AND OUTPUT: 50 PPM COLOR, 65 PPM B&W
- ▶ SIMITRI® HD TONER FOR SPECTACULAR COLOR QUALITY
- ▶ BIZHUB EXTENDED SOLUTION TECHNOLOGY (BEST) FOR INTEGRATING 3RD-PARTY SOFTWARE SOLUTIONS
- ▶ NEAR 100% PRODUCTIVITY WITH IMAGE STABILIZATION
- ▶ LARGE 8.5" COLOR TOUCH-SCREEN WITH THUMBNAIL PREVIEW
- ▶ BUILT-IN EMPERON® PRINT SYSTEM, PCL6/PS3 EMULATION, NATIVE XPS
- ▶ CUSTOMIZABLE "MYTAB" FOR QUICK ACCESS TO PRINT DRIVER SETTINGS
- ▶ NETWORK SCANNING INCLUDES SCAN-TO-ME, SCAN-TO-HOME, COLOR INTERNET FAX
- ▶ UP TO 6,650-SHEET PAPER CAPACITY FOR LONG PRINT/COPY RUNS
- ▶ EASIER USB ACCESS FOR PRINTING AND SCANNING
- ▶ STANDARD 250 GB HDD FOR HIGH-CAPACITY DOCUMENT STORAGE
- ▶ BOOKLET-MAKING, 100-SHEET STAPLING, Z-FOLD\*, POST INSERTER\* OPTIONS
- ▶ I-OPTION™ KITS FOR INTERNET ACCESS, SCANNING TO SHAREPOINT, ENHANCED SECURITY
- ▶ OPTIONAL SUPER G3 FAX, DUAL-LINE CAPABILITY
- ▶ FIERY® IMAGE CONTROL OPTION FOR ADVANCED COLOR GRAPHICS
- ▶ GREEN TECHNOLOGIES IN MANUFACTURING AND POWER-SAVING
- ▶ STANDARD SECURITY INCLUDING HDD JOB OVERWRITE, HDD SANITIZING AND HDD ENCRYPTION

\* Not available at time of launch.

The essentials of imaging

# bizhub C652



FULL COLOR\_PRINTER\_COPIER\_SCANNER\_FAX\_

CONNECT\_COMMUNICATE\_CONTROL\_

## General Specifications:

TYPE:	Full-Color Printer/Copier/Scanner with Stationary Platen
PRINT/COPY PROCESS:	Tandem Process
TONER TYPE:	Simitri® HD Toner
MONTHLY DUTY CYCLE:	250,000
PRINT/COPY SPEED:	Full Color: 50 ppm (letter, portrait), B&W: 65 ppm (letter, portrait) 1800 dpi equivalent x 600 dpi
PRINT/COPY RESOLUTION:	Full Color: 78 opm (@300dpi, letter), 55 opm (@ 600 dpi, letter), B&W: 78 opm (@300 dpi, letter), 65 opm (@ 600 dpi, letter) / 200 dpi, 300 dpi, 400 dpi, 600 dpi
SCAN FILE FORMATS:	TIFF, PDF, Compact PDF, JPEG, XPS, Compact XPS
MEMORY/HARD DISK DRIVE:	2 GB (shared print, copy, scan and fax memory)/250 GB HDD (shared print, copy, scan and fax)
GRADATION:	256 color shades per pixel
ORIGINAL SIZE:	Up to 11" x 17" (scanning/copying), Up to 11" x 17" full bleed on 12" x 18" paper (printing)
COPY SIZE:	Tray 1 (universal cassette): 5.5" x 8.5" to 12" x 18", Tray 2 (universal cassette): 5.5" x 8.5" to 12" x 18", Tray 3 (fixed cassette): 8.5" x 11" or 8.5" x 5.5", Tray 4 (fixed cassette): 8.5" x 11" or 8.5" x 5.5", Bypass Tray: 4" x 6" to 12" x 18"
WARM-UP TIME/FIRST COPY TIME:	Less than 30 seconds (from Sub SW), Less than 45 seconds (from Main SW) / Full Color: Less than 5.5 seconds (letter), B&W: Less than 3.8 seconds (letter)
COPY QUANTITY:	1 – 9,999
MAGNIFICATION:	Zoom range: 25% - 400%, 0.1% increments, Preset reduction: 79%, 73%, 65%, 50%, Preset enlargement: 121%, 129%, 155%, 200%
COLOR MODES:	Auto Color, Full Color, Black & White, 2-Color, Single Color
COPY EXPOSURE MODES:	Text (legible text), Text/Photo (clear text and halftones), Photo (optimized for gradations), Map (fine edges and legible text), Dot Matrix (dot matrix or pencil originals), Copied Paper
FAXING (optional):	Super G3 compatibility, MH, MR, MMR, JBIG data compression, 33.6 Kbps modem speed, F-Code support
FAX TRANSMISSION SPEED:	Less than 3 seconds/page (JBIG, standard resolution)
FAX MEMORY:	2 GB (shared print, copy, scan, fax memory)
FAX EXPOSURE MODES:	Text, Text/Photo, Photo, Dot Matrix
STANDARD PAPER CAPACITY:	500-sheet universal cassette (17 lb. bond to 140 lb. index), 500-sheet universal cassette (17 lb. bond to 140 lb. index), 1,000-sheet cassette (17 lb. bond to 140 lb. index), 1,500-sheet cassette (17 lb. bond to 140 lb. index), 150-sheet bypass (17 lb. bond to 100 lb. cover or up to 300 gsm)
MAXIMUM PAPER CAPACITY:	6,650 sheets (total, with options)
DOCUMENT FEEDER (standard):	Reversing Automatic Document Feeder, Speed: Full Color: 78 opm, B&W: 78 opm, Paper Capacity: 100 sheets, Paper Size: 5.5" x 8.5" to 11" x 17", Paper Weight: Single-sided: 9.25 lb. bond to 55.75 lb. bond, Double-sided or mixed: 13.25 lb. bond to 34 lb. bond
POWER REQUIREMENTS/CONSUMPTION:	120V, 60Hz/Less than 2,100W
DIMENSIONS (W x D x H)/WEIGHT:	25.56" x 30.56" (without control panel) / 34.63" (with control panel) x 42.50" (includes RADF) / 486.81 lb.
OPTIONS:	AU-102 Biometric Authentication Unit*, AU-201H HID Card Authentication Unit, EK-604 USB Host Board (Local I/F Kit), External Keyboard, FK-502 Fax Board, FS-526 100-Sheet Staple Finisher, KH-101 Keyboard Holder, LK-101 v2 i-Option, LK-102 i-Option, LU-204 Large Capacity Unit, LU-301 Large Capacity Unit, MK-720 Fax Connection Kit, OT-503 Output Tray (Exit Tray), PK-516 Punch Kit for FS-526 (2/3 Holes), SD-508 Saddle Stitch Kit for FS-526, Spare TX Marker Stamp 2, SP-501 Fax Stamp Unit, UK-203 i-Option Upgrade Kit, WT-506 Working Table, IC-412 Image Controller (EFI Fiery Controller), VI-505 Video Interface Kit for IC-412
AVAILABLE PRINT/COPY FUNCTIONS:	Account Track (1,000 accounts), Administration Mode, Auto Duplex, Auto Trapping, Auto Tray Switching, Bi-Directional Communication, Black Over Print, Color Modes & Functions (Auto Color/Full Color, Black & White Mode, Single Color Mode, 2-Color Mode, Color Adjustments - Brightness, Contrast, Saturation, Sharpness, Red, Green, Blue, Portrait, Hue, Density, Color Balance, Copy Density, Sample Copy), Copy Modes (Simplex/Duplex, 2-in-1, 4-in-1, 8-in-1, Book, Booklet, Booklet + Bind), Cover Mode, Creative Functions (Mirror Image, XY Zoom, Image Center, Base Color, Neg./Pos. Reverse, Image Repeat), Encrypted Network Password Printing, Energy Save Mode, Enlarge Display, Erase (Border, Frame, Edge) Mode, Finishing (Group, Sort, Staple, Punch, Half-Fold, Center Staple and Fold and Tri-Fold), Form Overlay, Glossy Mode, HDD Encryption, HDD Job, Overwrite, HDD Sanitizing, Image Adjustments (Color Matching, Pure Black Auto ON/OFF, Color Balance, Screen Settings, Image Smoothing ON/OFF), Image Preview (Job Finishing Image Display, Engine Configuration Display), Interrupt, Job List, Job Reserve, Job Skip, LDAP, OHP Interleaving, Mixplex, Mix-Media, MyTab, Non-image Area Erase, Program/Recall Jobs, Paper Type Selection (Normal, Thick 1/1+, Thick 2, Thick 3, Thick 4), Print Modes (Simplex/Duplex, 2-in-1, 4-in-1, 6-in-1, 9-in-1, 16-in-1, Booklet, Booklet + Bind), Print from USB, Proof Copy, Secure Printing, Separate Scan, Text Enhancement, User Authentication (Up to 20 Authentication Servers) (Synchronize w/Account Track), User Box Function, Utility (Meter Count, Environment Setting, Default Setting, One-Touch Setting, Check Consumables Life), Watermarks, Zoom Selection
AVAILABLE SCAN FUNCTIONS:	Scan-to-Email, Scan-to-FTP, Scan-to-HDD (Scan-to-User Box), Scan-to-Me/Scan-to-Home, Scan-to-SharePoint, Scan-to-SMB (Scan-to-Desktop), Scan-to-USB, Scan-to-WebDAV, Network TWAIN, WS-Scan, Color Internet Fax
AVAILABLE FAX FUNCTIONS:	Autodialing (2,000 one-touches), Auto Memory Reception, Auto Reduction Printing, Broadcasting (maximum 605 locations), Bulletin Board, Duplex Transmission/Reception, Exposure Mode, Group Dialing (up to 500 one-touches per group), Image Rotation Transmission/Reception, Mailbox Transmission/Reception, Memory/Quick Dial, Overseas Transmission, Password Transmission/Reception, PC-Fax, Polling Transmission/Reception, Priority Transmission, Print Setting or Overnight Reception, Program Dialing (400 programs), Redial, Relay Broadcasting, Relay Transmission, Remote Reception, Timer Transmission, TSI Routing
APPLICATIONS:	<b>Network &amp; Device Management:</b> PageScope EMS Plug-Ins, PageScope Net Care Device Manager, PageScope Network Setup, PageScope Data Administrator, Driver Packaging Utility, HDD Back-Up Utility, Download Manager (ICC Color Profile Utility), Log Management Utility, <b>User Tools:</b> PageScope Web Connection, PageScope Direct Print, PageScope Box Operator, PageScope Print Status Notifier, Web Print Assistant, Font Management Utility, Copy Protect Utility, Print Utility for Unix
MANAGEMENT TOOLS:	bizhub vCare support
OPTIONAL SOFTWARE:	<b>PageScope Enterprise Suite:</b> PageScope Account Manager, PageScope Authentication Manager, PageScope MyPanel Manager; PageScope Workware

## Emperon Print System (standard):

PROCESSOR:	1 GHz (MC 7448)
MEMORY/HARD DISK DRIVE:	2 GB (shared copier memory)/250 GB (shared copier HDD)
PAGE DESCRIPTION LANGUAGE:	PCL5e/c, PCL6 (XL v.3.0) Emulation, PS3 (v.3016) Emulation, XPS (XML Paper Specification)
FONTS:	PCL: 80 fonts, PostScript 3 Emulation: 137 fonts
PRINT DRIVERS:	<b>PCL6:</b> Windows 2000 Professional, Windows NT 4.0, Windows Server 2003 (x32, x64), Windows XP Home/Professional (x32, x64), Windows Vista (x32, x64), Windows Server 2008 (x32, x64) <b>PS3:</b> Windows 2000 Professional, Windows Server 2003 (x32, x64), Windows XP Home/Professional (x32, x64), Windows Vista (x32, x64), Windows Server 2008 (x32, x64) <b>XPS:</b> Windows Vista (x32, x64), Windows Server 2008 (x32, x64) <b>MAC:</b> Mac OS 9.2 (PPD file), Mac OS X 10.2, 10.3, 10.4, Intel-based 10.4 (print driver), Intel-based 10.5
INTERFACE:	10 BASE-T/100 BASE-TX/1000 BASE-T, USB 1.1, USB 2.0
PROTOCOLS:	TCP/IP, IPX/SPX, AppleTalk (EtherTalk), LPR, SMB, LPD, Netware (4.x, 5, 6), Pserver, Nprinter, NDPS, IPP 1.1, SMT, POP3, LDAP, SSL/TLS, SNMP, HTTP/HTTPS, IPv6, DPWS (WSD)

## Fiery IC-412 Embedded Image Controller (optional):

PROCESSOR:	Intel Celeron 1.86 GHz FSB 533 MHz
MEMORY/HARD DISK DRIVE:	512 MB (standard/max)/80 GB HDD
PAGE DESCRIPTION LANGUAGE:	PCL6, Adobe PostScript 3 (version 3017)
FONTS:	PCL: 80 fonts, Adobe PS3: 136 fonts
PRINT DRIVERS:	<b>PCL6:</b> Windows 2000, Windows XP, Windows Server 2003, Windows Vista (x32, x64) <b>PS3:</b> Windows 2000, Windows XP, Windows Server 2003, Windows XP Professional x64, Windows Server 2003 x64, Windows Vista (x32, x64), <b>Mac:</b> OS X 10.3.9, 10.4, Intel-based 10.4 (PPD), 10.5 or later Native Mode, Unix/Linux
INTERFACE:	10 BASE-T/100 BASE-TX/1000 BASE-T, RJ45
PROTOCOLS:	TCP/IP, IPX/SPX, AppleTalk (EtherTalk), LPR, SMB, NDPS Gateway on Netware 5.0 or later, IPP, LDAP, SSL/TLS, SNMP, HTTP/HTTPS, IPv6
STANDARD SOFTWARE:	EFI Command Workstation, ColorWise ProTools, EFI Spot-On, EFI WebTools
OPTIONAL SOFTWARE:	EFI Hot Folders/Virtual Printers, Auto Trapping, Color Profiler Suite, EFI Impose, Secure Erase, ES-1000 Spectrophotometer, ED-100 Desitometer



KONICA MINOLTA

bizhub



KONICA MINOLTA  
BUSINESS SOLUTIONS U.S.A., INC.  
100 Williams Drive  
Ramsey, NJ 07446  
[www.kmbs.konicaminolta.us](http://www.kmbs.konicaminolta.us)

© 2009 KONICA MINOLTA BUSINESS SOLUTIONS U.S.A., INC. All rights reserved. Reproduction in whole or in part without written permission is prohibited. Konica Minolta and The essentials of imaging are trademarks of KONICA MINOLTA HOLDINGS, INC. i-Option is a trademark and bizhub, Emperon and PageScope are registered trademarks of KONICA MINOLTA BUSINESS TECHNOLOGIES, INC. Simitri is a registered trademark of KONICA MINOLTA BUSINESS SOLUTIONS. All other brands and product names are registered trademarks or trademarks of their respective owners.

\*Not available at time of launch. \*\*This setting must be changed by an authorized Konica Minolta Service Technician.  
Design and specifications are subject to change without notice.

Item #: C652SS  
2/09